


This table helps you to identify the right STIEBEL unit depending on the number of fixture outlets that you wish to serve. Be aware that the table serves as general guidance only. If you require further assistance, please free call our national service centre on 1800 153 351.

Product Selection Guide for STIEBEL's Water Heaters

Please select 1 column

Water Heater	Model	Ideal Installation	Electrical Loading	Flow Rate & Temperature Rise	H × W × D in mm				
3-PHASE ELECTRIC INSTANTANEOUS	 DHE 27 AU 202659	› Kitchen sink (60°C) › Bathroom (suitable for use with a TMV) › Solar boosting › Commercial glass or dish washing	28.0 kW 40 Amps per Phase 3 Phase 415 V	Internally electronically controlled. Automatically adjusts flow to deliver right temperature.	466 × 225 × 116	3	2	3	4
	 DHE 18 AU 202658		19.4 kW 27 Amps per Phase 3 Phase 415 V			2	2	2	3
	 DEL 27 PLUS 236742	50°C › Delivers a maximum water temperature of 50°C (AS3498) › Kitchen sink (50°C) › Bathroom	28 kW 39 Amps per Phase 3 Phase 415 V	18 L/min = 22°C rise (= 2 showers mixed)	466 × 225 × 116	2	2	3	4
	 DEL 18 PLUS 236741	50°C	19.4 kW 27 Amps per Phase 3 Phase 415 V	15 L/min = 19°C rise (= 1 shower, 1 basin, mixed)		2	2	3	3
	 DEL 13 PLUS 234470	50°C	14.5 kW 20 Amps per Phase 3 Phase 415 V	12 L/min = 17°C rise (= 1 shower, 1 basin, mixed)		1	1	1	2
	 DHB-E 27 LCD 236749	› Kitchen sink (60°C) › Bathroom (suitable for use with a TMV) › Commercial glass or dish washing	28 kW 39 Amps per Phase 3 Phase 415 V	18 L/min = 22°C rise (= 2 showers mixed)	466 × 225 × 116	3	2	3	4
	 DHB-E 18 LCD 236748		19.4 kW 27 Amps per Phase 3 Phase 415 V	15 L/min = 19°C rise (= 1 shower, 1 basin, mixed)		2	2	2	3
	 DHB-E 13 LCD 236747		14.5 kW 20 Amps per Phase 3 Phase 415 V	12 L/min = 17°C rise (= 1 shower, 1 basin, mixed)		1	1	1	2
	 DHCE 8/60 233948	› Bathroom (suitable for use with a TMV) › 2 Basins › 1 Sink	9.5 kW 40 Amps Single phase 240 V (hard wired)	6 L/min = 23°C rise	360 × 200 × 110	1	0	1	2
	 DHCE 8/50 233640	50°C › Delivers a maximum water temperature of 50°C (AS3498) › 2 Basins › 1 Sink	9.5 kW 40 Amps Single phase 240 V (hard wired)	6 L/min = 23°C rise		1	0	1	2
SINGLE PHASE	 DHCE 6/50 233639	50°C	7.1 kW 30 Amps Single phase 240 V (hard wired)	6 L/min = 17°C rise		0	0	0	2
	 DEM 6 201683	50°C › 1 Basin	6.2 kW 25 Amps Single phase 240 V (hard wired)	4 L/min = 22°C rise	143 × 190 × 82	0	0	0	1

Water Heater	Model	Ideal Installation	Electrical Loading	Storage Capacity	H × W × D in mm
COMPACT STORAGE	 SNU 10 Plus	› 1 kitchen sink	2 kW 8.3 Amps Single phase 240 V (plug in)	10 litres	503 × 290 × 282
	 SNU 5 Plus	› Stores water up to 85°C		5 litres	423 × 240 × 212
	 SNE 5	› Must be fitted with STIEBEL's open vented tapware		5 litres	421 × 263 × 230
	 SHC 15 AU 235001	› Kitchen sink (60°C) › Can be used with any tapware › Suitable for more than 1 fixture outlet	1.6 kW 10 Amps Single phase 240 V (plug in)	15 litres	523 × 320 × 318
	 SHC 10 AU 235002			10 litres	498 × 280 × 270

Legend & Assumptions

-  shower(s)
-  sink(s)
-  basin(s)

Cold Water Temperature = 15°C
Mixed Water Temperature, delivered at outlet = 40°C
Shower Rise Flowrate 9 L/min
Sink Flowrate 7.5 L/min
Basin Flowrate 6 L/min

Water Heater	Model	Ideal Installation	Electrical Loading	Storage Capacity	H × W × D in mm
HEAT PUMP	 WWK 222/222H 231209 / 233209	› House › Suitable for 2-3 people household	0.55 kW 10 Amps Single phase 240 V	220 litres	ø 690 1553-1569 (adjustable feet)
	 WWK 302/302H 231211 / 232905	› House › Suitable for 4-6 people household	0.55 kW 10 Amps Single phase 240 V	302 litres	ø 690 1921-1937 (adjustable feet)

ELECTRIC INSTANTANEOUS HOT WATER - A MATTER OF PHYSICS

Instantaneous water heaters by STIEBEL ELTRON use electricity to produce hot water. The power needed depends on the cold water inlet temperature as well as the desired water flow rate: a low cold water temperature combined with high flow rates require a more powerful appliance to heat water.

COLD WATER INLET TEMPERATURE in QLD: approx. average of 18°C

$$\text{TEMPERATURE RISE (}^{\circ}\text{C)} = \frac{\text{kW rating} \times 14.3}{\text{flow rate (L/min)}}$$

The below chart shows the temperature rises that can be achieved by an electric instantaneous water heater based on its kW rating. To determine an approximate outlet temperature, add the below figure to the cold water temperature of your area.


EXAMPLE: A DHE 18 AU with a rated output of 19.4 kW comes with a temperature rise of approximately 40 °C at a flow rate of 7 L/min. Add 40 °C to a cold water temperature of 18 °C in Brisbane, and you get an approximate outlet temperature of 58 °C.

TEMPERATURE RISE CHART

Cold water temperature + temperature rise at certain flow rate = outlet temperature.
Please note that the maximum outlet temperature of each model will never be exceeded.

		Flow Rate in L/min													
Model	Rated Output	1.5	2.5	3	4	4.5	5	6	7	8	9	10	11	12	13
DHE 18 AU	19.4 kW		60 °C	60 °C	60 °C	60 °C	55 °C	45 °C	40 °C	35 °C	31 °C	28 °C	25 °C	23 °C	21 °C
DHE 27 AU	28.0 kW		60 °C	60 °C	60 °C	60 °C	60 °C	60 °C	59 °C	52 °C	46 °C	42 °C	38 °C	35 °C	32 °C
DEL 13 PLUS	14.5 kW			50 °C	50 °C	46 °C	41 °C	35 °C	30 °C	26 °C	23 °C	21 °C	19 °C	17 °C	
DEL 18 PLUS	19.4 kW		50 °C	50 °C	50 °C	50 °C	50 °C	46 °C	40 °C	35 °C	31 °C	28 °C	25 °C	23 °C	21 °C
DEL 27 PLUS	28.0 kW		50 °C	50 °C	50 °C	50 °C	50 °C	50 °C	50 °C	50 °C	44 °C	40 °C	36 °C	33 °C	31 °C
DHB-E 13 LCD	14.5 kW			60 °C	52 °C	46 °C	41 °C	35 °C	30 °C	26 °C	23 °C	21 °C	19 °C	17 °C	
DHB-E 18 LCD	19.4 kW			60 °C	60 °C	60 °C	55 °C	45 °C	40 °C	35 °C	31 °C	28 °C	25 °C	23 °C	21 °C
DHB-E 27 LCD	28.0 kW			60 °C	60 °C	60 °C	60 °C	60 °C	57 °C	50 °C	44 °C	40 °C	36 °C	33 °C	31 °C
DEM 6	6.2 kW		35°C	30 °C	22 °C	20°C	18 °C								
DHCE 6/50	7.1 kW	50 °C	41 °C	34 °C	26 °C	23 °C	20 °C	17 °C	15 °C	13 °C	11 °C				
DHCE 8/50	9.5 kW	50 °C	50 °C	45 °C	34 °C	30 °C	27 °C	23 °C	19 °C	17 °C	15 °C				
DHCE 8/60	9.5 kW	60 °C	54 °C	45 °C	34 °C	30 °C	27 °C	23 °C	19 °C	17 °C	15 °C				

*This is intended as a guide only. Installation, pipework and voltages can cause discrepancies.



For the most up to date product information, diagrams and data sheets head to stiebel-eltron.com.au/downloads

